

Labai ilgi gražtai metalui DIN1869

Fully ground extreme long twist drill DIN1869



Matmenys/Dimensions mm,

$\varnothing D$	L	L1
1,00	90	56
1,50	110	75
1,50	150	100
2,00	125	85
	160	110
	200	135
2,50	140	95
	180	120
	225	150
3,00	150	100
	190	130
	240	160
3,50	165	115
	210	145
	265	180
4,00	175	120
	220	150
	280	190
4,50	185	125
	235	160
	295	200
5,00	195	135
	245	170
	315	210
5,20	195	135
5,50	205	140
	260	180
	330	225
6,00	205	140
	260	180
	330	225

6,50	215	150
	275	190
	350	235
7,00	225	155
	295	200
	370	250
7,50	225	155
	295	200
	370	250
8,00	240	165
	305	210
	390	265
8,50	240	165
	305	210
	390	265
9,00	250	175
	320	220
	410	280
9,50	250	175
	320	220
	410	280
10,00	265	185
	340	235
	430	295
10,50	265	185
	340	235
	430	295
11,00	280	195
	365	250
	455	310
11,50	280	195
	365	250
	455	310
12,00	295	205
	380	260
	470	330
12,50	295	205
	375	260
	480	330
13,00	295	205
	375	260
	480	330

D – diametras mm,
L – bendras ilgis mm,
L1 – darbinis ilgis mm,

D – diameter mm,
L – length mm,
L1 – drilling part length mm